

The Fiber Optic Box ORM 3 SL 12S is designed for the placement of up to 12 optical splices both indoors and outdoors. The box may be complemented by a simple bracket for being post-mounted.

- ▶ Capacity of 12 optical splices
- ▶ Integrated fibre management
- ▶ 1× KM3 splice tray for the placement of optical splices
- ▶ Possibility of PLC splitter placement
- ▶ Placement of optical fiber reserve, length 3m
- ▶ Fixation of input/output cables
- ▶ Use only for fibers G657a,b
- ▶ Lid is fixed with screws
- ▶ Easy assembly
- ▶ Wall-mounted or post-mounted



TECHNICAL SPECIFICATIONS

Inputs / Outputs (quantity × range)	2× 3–9 mm, 9× 1.8–5 mm
Grommets (type and number of used grommets)	1× express port I.
Ingress Protection	IP54
Impact Protection	IK10
UV Resistance	yes
Flammability Degree	V0
Material	PC / ABS
Color	light gray RAL 7035
Dimensions (H × W × D)	136 × 136 × 46 mm
Weight	0.4 kg

ORDERING CODES

85K3.60/0000F	ORM 3 SL 12S
85K3.11/BAL0F	Pole Bracket for ORM 3

More information: <https://www.micostelcom.com/en/fiber-optic-boxes/fiber-optic-box-orm-3-sl-12s>

MICOS
TELCOM s.r.o.

+420 582 307 511
+420 582 307 688

telcom@micostelcom.cz
www.micostelcom.com