

GPON READY

5G READY

The ORM 4 optical distribution box is designed for the placement of 4 optical connectors both indoors and outdoors. The distribution box may be complemented by a simple bracket, which enables it to be post-mounted.

- ▶ Capacity of 4 optical connectors
- ▶ Connector holder SC, ST, FC, E2000, LC
- ▶ Placement of optical fiber reserve, length 1 m
- ▶ PG bushings
- ▶ Lockable lid
- ▶ Easy assembly
- ▶ Wall-mounted or post-mounted
- ▶ Coverage degree IP 54



TECHNICAL SPECIFICATIONS

Inputs / Outputs (quantity × range)	4 × 3 mm, 1 × 4–8 mm
Grommets (type and number of used grommets)	2 × PG16, 1 × PG9
Ingress Protection	IP54
Impact Protection	IK10
UV Resistance	yes
Flammability Degree	V0
Temperature Range	–40 °C / +70 °C
Material	PC / ABS
Color	light gray RAL 7035
Dimensions (H × W × D)	185 × 103 × 73 mm
Weight	0.6 kg
Environment	indoor outdoor
Number of Splices	1–12
Number of Connectors	1–12
Connector Type	SC LC E2000

ORDERING CODES

8170.71/0000F	Post bracket
8520.00/0000NBQ0125P--	ORM 4 holder 4×E2000, SC
8545.00/0000F	Base plate and cover

More information: <https://www.micostelcom.com/en/fiber-optic-boxes/orm-4-wall-mounted-optical-distribution-box>