

The optical distribution box ORU 3 is designed as a multi-purposed distributor with hinged rack for assembly up to 24 splice modules SAFeTNET for terminating or connecting of optical cables in micro-ducts or HDPE protecting pipes. Its construction enables using indoors and outdoors as well. With a simple holder it could be mounted on a pillar.

- ▶ Maximum capacity 864 optical splices
- ▶ Maximum connected capacity 288 subscribers (2 fibers for a subscriber)
- ▶ Maximum number of splice modules SAFeTNET 24 pcs.
- ▶ Placement of optical reserve, length 4 m
- ▶ Possibility of oval bushing installation for undivided cable (so-called „OMEGA“)
- ▶ Removable roof



## TECHNICAL SPECIFICATIONS

Inputs / Outputs (quantity × range)	12 × 23–46 mm
Grommets (type and number of used grommets)	12 × rubber grommet ø 50 mm
Ingress Protection	IP54
Impact Protection	IK10
UV Resistance	yes
Flammability Degree	V0
Material	glass reinforced polyester SMC
Color	light gray RAL 7035
Dimensions (H × W × D)	900 × 550 × 350 mm
Weight	23 kg

## ORDERING CODES

8509.00/000NF	ORU 3
8521.08/BAL0F	Post Brackets



More information: <https://www.micostelcom.com/en/fiber-optic-boxes/oru-3-wall-mounted-optical-distribution-box>

MICOS  
TELCOM s.r.o.

+420 582 307 511  
+420 582 307 688

telcom@micostelcom.cz  
[www.micostelcom.com](http://www.micostelcom.com)